

102 - 126 <sup>HP</sup>**DEUTZ-FAHR****5G HD SERIES****CAB**

If you're in the market for a universal tractor, the internationally renowned Deutz-Fahr 5G HD Series is worth serious consideration. Encompassing two models, 5105.4G and 5125G, delivering respective power outputs of 102 hp and 126 hp, the 5G HD tractors are perfect for livestock and arable farming, as well as vineyard operations.

Highly manoeuvrable, especially when fitted with a front end loader, the 5G HD tractors are packed with practical features, such as wet clutch Powershuttle, 4 wheel wet disc braking and Deutz-Fahr's Stop&Go technology. Loader work is made easy with integrated controls and the FARMotion common rail engine is economical to maintain and run.

**5105.4G HD**

40KM/H

**102HP****5125G HD**

40KM/H

**126HP****PHONE 1800 789 633****WE WORK BEYOND  
THE HORIZON.**

# TECHNICAL DATA & FEATURES

## 5105.4G HD CAB

## 5125G HD CAB

### POWER + PERFORMANCE

|                                |                      |        |
|--------------------------------|----------------------|--------|
| Engine Type                    | Deutz-Fahr FARMotion |        |
| Emissions                      | Tier III             |        |
| Cylinders / Capacity           | 4/3849               |        |
| Aspiration                     | Turbo Intercooler    |        |
| Max Power - 2000/25/EC (kW/HP) | 76/102               | 93/126 |
| Max Torque (Nm)                | 408                  | 500    |
| Rated Engine Speed (rpm)       | 2200                 |        |
| Fuel Capacity (l)              | 150                  |        |

### DRIVE + HANDLING

|                                      |                                    |                 |
|--------------------------------------|------------------------------------|-----------------|
| Gearbox Type and Gears               | Wet Clutch Power Shuttle           |                 |
| Number of Gears                      | 40+40                              | 60+60           |
| Powershift Speeds                    | 2                                  | 3               |
| Speed Matching Powershift            |                                    | ■               |
| Forward/Reverse Sense Clutch Shuttle | ■                                  |                 |
| STOP & Go                            | ■                                  |                 |
| Min Speed (km/h)                     | 0.22                               | 0.12            |
| Max Speed (km/h)                     | 40 ECO                             |                 |
| 4WD + 4 Wheel Diff Lock              | ■                                  |                 |
| Brakes (NO / Type)                   | 4/ Independent Wet Disc            |                 |
| Wheel Size - Rear                    | Adjustable 480/70R38               | Fixed 540/65R38 |
| Wheel Size - Front                   | Adjustable 420/70R24               | Fixed 440/65R28 |
| PTO Type                             | Electro-Hyd Independent Wet Clutch |                 |
| Speeds - Rear                        | 540/540E/1000/1000E                |                 |
| PTO engine speed (rpm)               | 1958/1650/1960/1643                |                 |

### LIFT + FLOW

|                               |                                                         |                                          |
|-------------------------------|---------------------------------------------------------|------------------------------------------|
| Type                          | Open Centre                                             | On Demand                                |
| Flow Rate (l/min)             | Mechanical / Steering 40 - Hydraulics 55                | Mechanical / Steering 40 - Hydraulics 90 |
| Remote Valves (Sets/Type)     | 3 / (1 Kickout / 1 Detent / 1 Float)                    | 3 / (3 Float / 3 Detent)                 |
| Flow Control on Remote Valves | 1 Valve                                                 | All Valves                               |
| 3 Point Hitch Type            | AGROTRONIC Electronic Hitch c/w external fender control |                                          |
| Category                      | 2                                                       |                                          |
| Hitch End Type                | Hook                                                    |                                          |
| Max Lift Capacity - Rear (kg) | 3600                                                    | 5410                                     |

### COMFORT + CONVENIENCE

|                                             |                    |                    |
|---------------------------------------------|--------------------|--------------------|
| Air-Conditioned Cabin                       | ■                  |                    |
| Radio/MP3 Player                            | ■                  |                    |
| Silent Block Cab Suspension                 | Optional           | ■                  |
| Cloth Driver Seat with Pneumatic Suspension | ■                  |                    |
| Trainee Seat                                | Optional           |                    |
| Adjustable Steering Wheel                   | ■                  |                    |
| InfoCentre Dash                             | ■                  |                    |
| Engine Speed Programming                    | ■                  |                    |
| Hi Vis Roof                                 | ■                  |                    |
| SDD Steering                                | -                  | ■                  |
| Upswept Side Mounted Exhaust                | ■                  |                    |
| Worklights (No + Type)                      | 4 Bonnet / 4 Cabin | 4 Bonnet / 6 Cabin |

### WEIGHTS + DIMENSIONS

|                        |      |      |
|------------------------|------|------|
| Wheelbase (mm)         | 2400 |      |
| Length (mm)            | 4270 | 4314 |
| Mid Overall Width (mm) | 2186 | 2320 |
| Height (mm)            | 2700 | 2730 |
| Weight (kg)            | 4300 | 4400 |

■ Standard



#### COMFORTABLE WORKING AREA



#### INTEGRATED FRONT END LOADER CONTROL



#### SENSE CLUTCH POWERSHUTTLE



#### FARMOTION COMMON RAIL DIESEL ENGINE



#### ON DEMAND 90L/MIN HYDRAULICS (5125G)

